

FLRYW-A | 歐規薄肉耐熱汽車花線 ISO Thin Wall Heat-Resistant Wire with Symmetric Conductor (Type A)

產品說明 PRODUCT DESCRIPTION

*類別: ■ ■ 歐規薄肉耐熱汽車花線

*導體: 符合 ISO 6722 規範軟銅絞線 Stranded copper conductor

*絕緣: PVC 材質, 符合 ISO 6722 及 ROHS 規範 PVC Insulation

*耐溫: -40~125℃

*多種顏色選擇 Any colors for customized



FLRYW-A 歐規薄肉耐熱汽車花線，適用於汽車、機車及各式運送工具之歐規薄肉低壓絕緣花線，符合 ISO 6722 規範。

FLRYW-A Heat-resistant low tension wire with thin wall insulation, suitable for automobiles, motorcycles, and other motor vehicles. ISO 6722 compliant.

FLRYW-A | ISO Thin Wall Heat-Resistant Wire with Symmetric Conductor (Type A)

公稱截面積 mm ²	導體結構 mm X no.	絞合外徑 Overall Diameter	絕緣厚度		完成外徑	外被披覆 Material
			標準	最小	標準	
0.22 mm ²	0.20 mm / 7	0.7 mm	0.25 mm	0.20 mm	1.2 mm	PVC
0.35 mm ²	0.26 mm / 7	0.8 mm	0.25 mm	0.20 mm	1.3 mm	PVC
0.5 mm ²	0.19 mm / 19	1.0 mm	0.28 mm	0.22 mm	1.6 mm	PVC
0.75 mm ²	0.23 mm / 19	1.2 mm	0.30 mm	0.24 mm	1.9 mm	PVC
1.0 mm ²	0.26 mm / 19	1.3 mm	0.30 mm	0.24 mm	2.1 mm	PVC
1.5 mm ²	0.32 mm / 19	1.7 mm	0.30 mm	0.24 mm	2.4 mm	PVC
2.0 mm ²	0.36 mm / 19	2.0 mm	0.35 mm	0.28 mm	2.8 mm	PVC
2.5 mm ²	0.41 mm / 19	2.1 mm	0.35 mm	0.28 mm	3.0 mm	PVC

大域科技股份有限公司

TA YU SCIENCE Co., Ltd



+886-3-329-8989



+886-3-329-7811



tayui@ms24.hinet.net



benson@tayui.com.tw



www.tayui.com.tw