


VS



泰亦膠業股份有限公司

TAY YAH RUBBER INDUSTRY Co.,Ltd.

桃園市中壢區環北路602號 03-452-9941 tayyah4@yahoo.com.tw



VS型軸向油封 尺寸規格表

*Unit:mm

No.	VS規格	內徑I.D.	外徑O.D.	油封高度H	內環厚度B	適用軸徑C
1.	VS-5	4	8	5.2	3.9	4.5-5.5
2.	VS-6	5	9	5.2	3.9	5.5-6.5
3.	VS-7	6	10	5.2	3.9	6.5-8
4.	VS-8	7	11	5.2	3.9	8-9.5
5.	VS-10	9	15	7.7	5.6	9.5-11.5
6.	VS-12	10.5	16.5	7.7	5.6	11.5-13.5
7.	VS-14	12.5	18.5	7.7	5.6	13.5-15.5
8.	VS-16	14	20	7.7	5.6	15.5-17.5
9.	VS-18	16	22	7.7	5.6	17.5-19
10.	VS-20	18	26	10.5	7.9	19-21
11.	VS-22	20	28	10.5	7.9	21-24
12.	VS-25	22	30	10.5	7.9	24-27
13.	VS-28	25	33	10.5	7.9	27-29
14.	VS-30	27	35	10.5	7.9	29-31
15.	VS-32	29	37	10.5	7.9	31-33
16.	VS-35	31	39	10.5	7.9	33-36
17.	VS-38	34	42	10.5	7.9	36-38
18.	VS-40	36	46	13	9.5	38-43
19.	VS-45	40	50	13	9.5	43-48
20.	VS-50	45	55	13	9.5	48-53
21.	VS-55	49	59	13	9.5	53-58
22.	VS-60	54	64	13	9.5	58-63
23.	VS-65	58	68	13	9.5	63-68
24.	VS-70	63	75	15.5	11.3	68-73
25.	VS-75	67	79	15.5	11.3	73-78
26.	VS-80	72	84	15.5	11.3	78-83
27.	VS-85	76	88	15.5	11.3	83-88
28.	VS-90	81	93	15.5	11.3	88-93
29.	VS-95	85	97	15.5	11.3	93-98
30.	VS-100	90	102	15.5	11.3	98-105
31.	VS-110	99	113	18	13.1	105-115
32.	VS-120	108	122	18	13.1	115-125
33.	VS-130	117	131	18	13.1	125-135
34.	VS-140	126	140	18	13.1	135-145
35.	VS-150	135	149	18	13.1	145-155
36.	VS-160	144	160	20.5	15	155-165
37.	VS-170	153	169	20.5	15	165-175
38.	VS-180	162	178	20.5	15	175-185
39.	VS-190	171	187	20.5	15	185-195
40.	VS-199	180	196	20.5	15	195-210