




HEAT SHRINKABLE-SPADE TERMINALS "HB"(BRAZED TYPE)

MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18	16	14	12	10	8
--------	----	----	----	----	----	----	----	---

AMP.	9	12	17	18	30	35	50	70
------	---	----	----	----	----	----	----	----

MAXIMUM ELECTRICAL RATING : 600 VOLTS MAX.
SHRINK TEMP. : 150°C OPERATING TEMP. :-10°C ~ +105°C
INSULATION MATERIAL : HIGH DENSITY PE.
TERMINAL MATERIAL : COPPER


WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION						INSULATED COLOR	CRIMPING TOOL	Q'TY BOX
		d2		W		L				
		inch	mm	inch	mm	inch	mm			
22-16 A.W.G. 0.5-1.5 mm ²	SHBL1-3.7	#6	3.7	.252	6.4	1.154	29.3	RED	K.S. MODEL KST2000G WITH DIE INDEX NO:1	1000
	SHBM1-4	#8	4.3	.283	7.2	1.165	29.6			1000
	SHBL1-5	#10	5.3	.374	9.5	1.181	30.0			1000
16-14 A.W.G. 1.5-2.5 mm ²	SHBL2-3.7	#6	3.7	.236	6.0	1.122	28.5	BLUE	K.S. MODEL KST2000G WITH DIE INDEX NO:2	500
	SHBM2-4	#8	4.3	.283	7.2	1.161	29.5			500
	SHBL2-5	#10	5.3	.366	9.3	1.201	30.5			500
12-10 A.W.G. 4-6 mm ²	SHBL5-4	#8	4.3	.354	9.0	1.319	33.5	YELLOW	K.S. MODEL KST2000G WITH DIE INDEX NO:5	500
	SHB5-5	#10	5.3							500
	SHBL5-6	1/4	6.4	.472	12.0	1.614	41.0			500
8 A.W.G. 8 mm ²	SHB8-5	#10	5.3	.413	10.5	1.358	34.5	RED	K.S. MODEL LY-2045D OR IZUMI MODEL 8 WITH DIE INDEX NO:8	500
	SHB8-6	1/4	6.4	.425	10.8	1.417	36.0			