



聚乙烯 PE 為基材。環保無鹵素照射線，經過輻照交連作用，具備優異的耐熱性、耐寒性、抗化學與耐磨等特性。

The Polyethylene (PE) base material. Environmentally and halogen-free radiation hook up wire, after cross-linking, it has excellent heat resistance, cold resistance, chemical resistance and abrasion resistance

UL3321 - 150°C 600V(STRANDED 絞線)

MODEL	導體結構	絕緣厚度	完成外徑	英制	公制
AWG	NO.X MM	INS THK	OVERALL DIA	FT/COIL	M/COIL
24AWG	11 / 0.16	0.81 mm	2.23 mm ± 0.05	2000FT	610 M
22AWG	17 / 0.16	0.81 mm	2.38 mm ± 0.05	2000FT	610 M
20AWG	21 / 0.18	0.81 mm	2.57 mm ± 0.05	2000FT	610 M
18AWG	34 / 0.18	0.83 mm	2.80 mm ± 0.05	2000FT	610 M
16AWG	26 / 0.254	0.85 mm	3.20 mm ± 0.05	2000FT	610 M
14AWG	41 / 0.254	0.85 mm	3.60 mm ± 0.05	1000FT	305 M
12AWG	65 / 0.254	0.85 mm	4.07 mm ± 0.05	1000FT	305 M



聚乙烯 PE 為基材。環保無鹵素照射線，經過輻照交連作用，具備優異的耐熱性、耐寒性、抗化學與耐磨等特性。

The Polyethylene (PE) base material. Environmentally and halogen-free radiation hook up wire, after cross-linking, it has excellent heat resistance, cold resistance, chemical resistance and abrasion resistance

UL3385 - 105°C 300V(STRANDED 絞線)

MODEL	導體結構	絕緣厚度	完成外徑	英制	公制
AWG	NO.X MM	INS THK	OVERALL DIA	FT/COIL	M/COIL
28AWG	7 / 0.127	0.40 mm	1.18 mm ± 0.05	2000FT	610 M
26AWG	7 / 0.16	0.40 mm	1.28 mm ± 0.05	2000FT	610 M
24AWG	11 / 0.16	0.40 mm	1.41 mm ± 0.05	2000FT	610 M
22AWG	17 / 0.16	0.40 mm	1.56 mm ± 0.05	2000FT	610 M
20AWG	21 / 0.18	0.40 mm	1.76 mm ± 0.05	2000FT	610 M
18AWG	34 / 0.18	0.40 mm	2.07 mm ± 0.05	2000FT	610 M
16AWG	26 / 0.254	0.40 mm	2.40 mm ± 0.05	1000FT	305 M

大域科技股份有限公司

TA YU SCIENCE Co., Ltd

+886-3-329-8989

+886-3-329-7811

tayui@ms24.hinet.net

benson@tayui.com.tw

www.tayui.com.tw



聚乙烯 PE 為基材。環保無鹵素照射線，經過輻照交連作用，具備優異的耐熱性、耐寒性、抗化學與耐磨等特性。

The Polyethylene (PE) base material. Environmentally and halogen-free radiation hook up wire, after cross-linking, it has excellent heat resistance, cold resistance, chemical resistance and abrasion resistance

UL3386 - 105°C 600V(STRANDED 絞線)

MODEL	導體結構	絕緣厚度	完成外徑	英制	公制
AWG	NO.X MM	INS THK	OVERALL DIA	FT/COIL	M/COIL
26AWG	7 / 0.16	0.80 mm	2.08 mm ± 0.05	2000FT	610 M
24AWG	11 / 0.16	0.80 mm	2.21 mm ± 0.05	2000FT	610 M
22AWG	17 / 0.16	0.80 mm	2.36 mm ± 0.05	2000FT	610 M
20AWG	21 / 0.18	0.80 mm	2.56 mm ± 0.05	2000FT	610 M
18AWG	34 / 0.18	0.80 mm	2.87 mm ± 0.05	2000FT	610 M
16AWG	26 / 0.254	0.85 mm	3.20 mm ± 0.05	1000FT	305 M
14AWG	41 / 0.254	0.85 mm	3.60 mm ± 0.05	1000FT	305 M
12AWG	65 / 0.254	0.85 mm	4.10 mm ± 0.05	1000FT	305 M
10AWG	105 / 0.254	0.85 mm	4.70 mm ± 0.05	1000FT	305 M