



FX- 5780 FIXED 2D SCANNER

Physical Characteristics	
Dimensions (L x W x H) :	35mm x 35.5mm x 20.2mm
Weight:	70g
Input Voltage:	USB: 5V ; RS-232: 3.3V
Current:	RS-232: 250mA (Operating); 71mA (Idle); 2.7mA (Sleep Mode) USB: 200mA (Operating); 55mA (Idle); 2.1mA (Suspend)
Performance Characteristics	
Barcode Engine	Honeywell N5780
Image:	CMOS sensor 1280 x 800 pixels; Global Shutter; up to 60 frames per second
Light Source:	Aiming: Green Cross LED; Illumination: White LED
Field OF View:	Horizontal: 47° ; Vertical: 30°
Scan Angles:	Tilt: 360° ; Pitch: ±60° ; Skew: ±60°
Print Contrast:	20% minimum print contrast ratio
Motion Tolerance:	6 meter per second
Symbology Decode Capability	
1D:	Codabar, Code 11, Code 128, Code 2 of 5, Code 39, Code 93 and 93i, EAN/JAN-13, EAN/JAN 8, IATA Code 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI, GS1 DataBar, UPC-A, UPC-E, UPC-A/EAN-13 with Extended Coupon Code, Coupon GS1 Code 32 (PARAF), EAN-UCC Emulation
2D:	Codablock A, Codablock F, PDF417, MicroPDF417, Aztec Code, Data Matrix, Maxi Code, QR Code, Chinese Sensible(Han Xin) Code, DotCode, Grid Matrix
Postal Codes:	Australian Post, British Post, Canadian Post, China Post, Japanese Post, Korea Post, Netherlands Post, Planet Code, Postnet
OCR	OCR-A, OCR-B, MICR-13, Digimarc Barcode
Environmental	
Temperature:	Operating: -30°C to 60°C ; Storage: -40°C to 70°C
Humidity:	0% to 95% relative humidity, non-condensing, at 60°C
Ambient Light:	0 – 100,000 lux
Shock Specification	Designed to withstand 1.5m(5') drops
Decode Range	
100% U.P.C	40mm to 490mm
5 mil Code 39	60mm to 275mm
20 mil QR Code	27mm to 440mm
Performance may be impacted by barcode quality and environmental conditions.	

ALL FUN Enterprise CO., LTD

Tel: +886-2-2946-6556 Fax: +886-2-2946-4678

Add: 13F, No.126-1, Huaxin St., Zhonghe Dist., New Taipei City 235, Taiwan