




HEAT SHRINKABLE-RING TERMINALS "HB"(BRAZED TYPE)

MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18	16	14	12	10	8
AMP.	9	12	17	18	30	35	50	70

MAXIMUM ELECTRICAL RATING : 600 VOLTS MAX.
SHRINK TEMP. : 150°C OPERATING TEMP. :-10°C ~ +105°C
INSULATION MATERIAL : HIGH DENSITY PE.
TERMINAL MATERIAL : COPPER


WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION						INSULATED COLOR	CRIMPING TOOL	Q'TY BOX
		d2		W		L				
		inch	mm	inch	mm	inch	mm			
22-16 A.W.G. 0.5-1.5 mm ²	RHBS1-3.7	#6	3.7	.217	5.5	.984	25.0	RED	K.S. MODEL KST2000G WITH DIE INDEX NO:1	1000
	RHBL1-4	#8	4.3	.315	8.0	1.122	28.5			1000
	RHB1-5	#10	5.3							1000
	RHB1-6	1/4	6.4	.457	11.6	1.358	34.5			500
	RHB1-8	5/16	8.4							500
	RHB1-10	3/8	10.5							.535
16-14 A.W.G. 0.5-2.5 mm ²	RHBS2-3.7	#6	3.7	.260	6.6	1.043	26.5	BLUE	K.S. MODEL KST2000G WITH DIE INDEX NO:2	1000
	RHBL2-4	#8	4.3	.335	8.5	1.201	30.5			1000
	RHBL2-5	#10	5.3	.374	9.5					1000
	RHB2-6	1/4	6.4	.472	12.0	1.398	35.5			500
	RHB2-8	5/16	8.4							500
	RHB2-10	3/8	10.5							.535
12-10 A.W.G. 4-6 mm ²	RHBL5-4	#8	4.3	.374	9.6	1.346	34.2	YELLOW	K.S. MODEL KST2000G WITH DIE INDEX NO:5	500
	RHB5-5	#10	5.3			1.339	34.0			500
	RHB5-6	1/4	6.4	.472	12.0	1.476	37.5			500
	RHB5-8	5/16	8.4	.591	15.0	1.654	42.0			500
	RHB5-10	3/8	10.5							500
	RHB5-12	1/2	13.0	.756	19.2	1.831	46.5			500
8 A.W.G. 8 mm ²	RHBM8-5	#10	5.3	.472	12.0	1.457	37.0	RED	K.S. MODEL LY-2045D OR IZUMI MODEL 8 WITH DIE INDEX NO:8	500
	RHBS8-6	1/4	6.4							500
	RHB8-8	5/16	8.4	.591	15.0	1.693	43.0			500
	RHB8-10	3/8	10.5							500