

產品說明 PRODUCT DESCRIPTION

- *類別:  美規超薄肉 XLPE 照射汽車花線
- *導體: 符合 ASTM B3 規範軟銅絞線 Stranded copper conductor
- *絕緣: **XLPE 材質**, 符合 SAE J1678 及 ROHS 規範 XLPE Insulation
- *耐溫: **-40~125℃**
- *多種顏色選擇 Any colors for customized



WXC 美規超薄肉 XLPE 照射汽車花線，適用於汽車、機車及各式運送工具之美規耐熱厚肉低壓 XLPE 絕緣花線。

TXL Heat-resistant low-tension XLPE wire with ultra thin wall, suitable for automobiles, motorcycles, and other motor vehicles. SAE J1768 compliant.

WXC | (SAE Ultra Thin Wall XLPE Wire)

美規公稱 AWG	導體結構 mm X no.	絞合外徑 Overall Diameter	絕緣厚度		完成外徑	外被披覆 Material
			標準	最大	標準	
24 AWG	0.20 mm / 7	0.6 mm	0.25 mm	0.20 mm	1.15 mm ±0.05	XLPE
22 AWG	0.26 mm / 7	0.8 mm	0.25 mm	0.20 mm	1.35 mm ±0.05	XLPE
20 AWG	0.32 mm / 7	1.0 mm	0.25 mm	0.20 mm	1.60 mm ±0.05	XLPE
20 AWG	0.19 mm / 19	1.0 mm	0.25 mm	0.20 mm	1.60 mm ±0.05	XLPE
18 AWG	0.23 mm / 19	1.2 mm	0.25 mm	0.20 mm	1.80 mm ±0.05	XLPE
16 AWG	0.29 mm / 19	1.5 mm	0.25 mm	0.20 mm	2.10 mm ±0.05	XLPE
14 AWG	0.36 mm / 19	1.8 mm	0.25 mm	0.20 mm	2.40 mm ±0.05	XLPE
12 AWG	0.45 mm / 19	2.3 mm	0.30 mm	0.24 mm	3.00 mm ±0.05	XLPE

大域科技股份有限公司

TA YU SCIENCE Co., Ltd

 **+886-3-329-8989**

 **+886-3-329-7811**

 **tayui@ms24.hinet.net**

 **benson@tayui.com.tw**

 **www.tayui.com.tw**