



Access control security system

www.jantek.com.tw

PB-N71 / N86

Infrared Push Button

(Proximity Button & Exit button)



✉ iapetus@jantek.com.tw

ACCESS CONTROL SYSTEM / PROXIMITY CARD READER
MIFARE READER / MIFARE MODULE / FINGERPRINT READER
TIME AND ATTENDANCE SYSTEM / ELECTRIC DOOR BOLT
ACCESSORIES / COPIER CONTROLLER / PUSH BUTTON

Taiwan Jantek Electronics Ltd.

Tel : 886-2-2299-1255(Rep.) | Fax : 886-2-2299-1257 / 2299-7412

6F-1, No. 1, Wuquan 1St.Rd.,Xinzhuang District, New Taipei City 24892,Taiwan,

Features :

- The Contactless, feature means sterile and hygienic.
- Under normal situation with blue LED. When it is active, LED turns to Green. It's easy to indicate the operation status.
- Relay trigger time is adjustable from 1 to 9 seconds
- Proximity distance is adjustable from 5 to 20 cm.
- Offer one touch point to operate when infrared is abnormal.
- Indoor only.
- Remote control door open with an infrared keypad. (Option Device)

Specifications :

- Dimension: ·PB-N71 116 (L) X 71 (W) X 37 (H) mm
·PB-N86 86 (L) X 86 (W) X 37 (H) mm
- Contact Rating: 0.5A 125VAC / 2A 30VDC / 0.3A 110VDC
- Contact Type: 2 form C (DPDT)
- Relay Life: Mechanical:100,000,000 times / Electrical:500,000 times
- Operation Temperature: -20℃ ~ 55℃
- LED indicate: Blue: normal / Green:active
- Offer one touch point to operate when infrared is abnormal
- Relay trigger time : 1 to 9 second (adjustable)
- Stainless steel faceplate
- Operation Distance: From 5 ~ 20 cm (adjustable)
- Operation Voltage: DC9V ~ DC12V

