

MAP® UL1107 UL1365 COAXIAL CABLE

產品說明 PRODUCT DESCRIPTION

*導體為軟銅線或鍍錫銅 Bare copper or Tinned copper conductor

*聚乙烯或耐燃聚乙烯絕緣 PE or FRPE insulation

*鍍錫銅或裸銅編織網隔離 TC or Bare copper braid shield

*低損耗,傳輸效率高 Low loss and high transmission efficiency.

*額定溫度 60°C Rated temperature 60 °C

*額定電壓 300V Rated voltage:300V

* 符合 UL VW-1 燃燒測試 Available UL &CSA flame test.





Coaxial cable UL1107 .UL1365.

高解析/高清 同軸電纜專用,廣泛使用於通訊設備/監視器/移動式攝影機等產品。公共建設、大眾運輸系統、智能家庭、保全系統指定用線。

High resolution / HD coaxial cable, used in communications equipment / monitors / portable cameras and so on. Public construction, mass transit system, intelligent home, preservation system for application.

Coaxial cable UL1107 UL1365

STYLE	AWG	NO. OF COND.	INS THK	BRAID SHIELD	JACKET THK	OVERALL DIAMETER
UL1107 (stranded)	30	7/0.102	0.4 mm	16/4/0.102	0.4 mm	2.4 mm ±0.1
UL1107 (stranded)	28	7/0.127	0.4 mm	16/4/0.102	0.4 mm	2.5 mm ±0.1
UL1107 (stranded)	26	7/0.160	0.4 mm	16/4/0.127	0.4 mm	2.8 mm ±0.1
UL1107 (stranded)	24	7/0.203	0.4 mm	16/4/0.127	0.4 mm	2.9 mm ±0.1
UL1107 (stranded)	22	7/0.255	0.4 mm	16/4/0.127	0.6 mm	3.3 mm ±0.15
UL1107 (solid)	30	1/0.254	0.4 mm	16/4/0.102	0.4 mm	2.4 mm ±0.1

STYLE	AWG	NO. OF COND.	INS THK	BRAID SHIELD	JACKET THK	OVERALL DIAMETER
UL1365 (stranded)	30	7/0.102	0.66 mm	16/5/0.102	0.4 mm	3.0 mm ±0.1
UL1365 (stranded)	28	7/0.127	0.66 mm	16/5/0.102	0.4 mm	3.2 mm ±0.15
UL1365 (stranded)	26	7/0.160	0.66 mm	16/5/0.127	0.4 mm	3.3 mm ±0.15
UL1365 (stranded)	24	7/0.203	0.66 mm	16/5/0.127	0.4 mm	3.4 mm ±0.15
UL1365 (solid)	30	7/0.255	0.66 mm	16/5/0.127	0.4 mm	3.0 mm ±0.15

大域科技股份有限公司

 +886-3-329-8989

 tayui@ms24.hinet.net

 www.tayui.com.tw

TA YU SCIENCE Co., Ltd

 +886-3-329-7811

 benson@tayui.com.tw

