

MAP® CERAMICS FELT WITH SILICA FIBER BRAID

陶瓷纖維+二氧化矽纖維編織高溫線 耐溫 **750C**,耐壓 600V

產品說明 PRODUCT DESCRIPTION

*導體:純鎳線 Pure Nickel Conductor

*編織:陶瓷纖維+二氧化矽纖維編織 Ceramics Felt with Silica Fiber Braid

*額定溫度 750°C Rated temperature 750°C

*額定電壓 600 伏特 Rated voltage: 600V

*柔軟/耐高溫/耐寒 Flexible/High temperature resistant/Cold-resistant

*符合 ROHS 環保規範 Available ROHS NORM





適用於高功率設備&高溫環境:工控、儀器儀表、電熱加溫設備、金屬熔爐、熱熔高溫爐。

Suitable for high-power equipment & high temperature environment: industrial control, instrumentation, electric heating equipment, metal furnace, hot-melt high temperature furnace.

耐溫:750℃ 耐電壓:600V ,編織材質:陶瓷纖維+二氧化矽纖維編織 Ceramics Felt with Silica Fiber Braid

MAP® 750℃ 陶瓷纖維+二氧化矽纖維編織 (STRANDEED)

SIZE	SIZE	導體結構	陶瓷纖維厚度	二氧化矽纖維厚度	完成外徑
MM ²	AWG	NO.X MM	CERAMICS FELT	SILICA FIBER	OVERALL DIA
0.3 mm ²	22AWG	4/0.3 mm	0.25 mm	0.16 mm	1.52 mm ± 2%
0.5 mm ²	20AWG	7/0.3 mm	0.25 mm	0.16 mm	1.65 mm ± 2%
0.75 mm ²	18 AWG	10/0.3 mm	0.35 mm	0.16 mm	2.25 mm ± 2%
1.0 mm ²	17 AWG	14/0.3 mm	0.35 mm	0.16 mm	2.40 mm ± 2%
1.25 mm ²	16 AWG	18/0.3 mm	0.35 mm	0.16 mm	2.75 mm ± 2%
1.5 mm ²	15 AWG	23/0.3 mm	0.35 mm	0.16 mm	2.95 mm ± 2%
2.0 mm ²	14 AWG	28/0.3 mm	0.35 mm	0.16 mm	3.10 mm ± 2%
2.5 mm ²	13 AWG	35/0.3 mm	0.45 mm	0.39 mm	3.50 mm ± 2%
3.5 mm ²	12 AWG	49/0.3 mm	0.45 mm	0.39 mm	4.28 mm ± 2%
4.0 mm ²	11 AWG	56/0.3 mm	0.45 mm	0.39 mm	4.50 mm ± 2%
5.5 mm ²	10 AWG	77/0.3 mm	0.45 mm	0.39 mm	4.80 mm ± 2%
6.0 mm ²	10 AWG	84/0.3 mm	0.45 mm	0.39 mm	5.00 mm ± 2%
8.0 mm ²	8 AWG	112/0.3 mm	0.45 mm	0.39 mm	5.30 mm ± 2%
10 mm ²	7AWG	140/0.3 mm	0.45 mm	0.39 mm	6.10 mm ± 2%
14 mm ²	6AWG	196/0.3 mm	0.45 mm	0.39 mm	6.58 mm ± 2%
16 mm ²	5 AWG	224/0.3 mm	0.45 mm	0.39 mm	7.60 mm ± 2%
22 mm ²	4 AWG	308/0.3 mm	0.55 mm	0.39 mm	8.50 mm ± 2%

大域科技股份有限公司

TA YU SCIENCE Co., Ltd

+886-3-329-8989

+886-3-329-7811

tayui@ms24.hinet.net

benson@tayui.com.tw

www.tayui.com.tw