


SKINDICHT® SH

Nickel-plated brass cable clamp with single saddle clamp and PG thread



Complete the installation

SKINDICHT®
SM locknuts
page 542

The SKINDICHT® SH cable clamp is an extremely durable compact strain relief cable gland constructed of corrosion-resistant nickel-plated brass. Strain relief is achieved by use of a specially formed nickel-plated brass bracket that provides a secure locking system.

Approvals



Technical data



Material:

- body:

nickel-plated brass



Temperature range:

-20°C to +200°C



Locknuts:

add SKINDICHT® SM, page 542



IP Protection:

IP20

Part number	Thread	Clamping range (øF)		Wrenching flats (SW) in	Overall length (C) in	Thread length (D) in	Max. installation diameter in	Pack size
		in	mm					
52000830	PG 7	0.315 - 0.394	8.0 - 10.0	0.591	0.689	0.216	0.866	50
52000840	PG 9	0.394 - 0.492	10.0 - 12.5	0.669	0.807	0.236	0.985	50
52000850	PG 11	0.433 - 0.591	11.0 - 15.0	0.788	0.847	0.236	1.103	50
52000860	PG 13	0.551 - 0.650	14.0 - 16.5	0.866	0.945	0.295	1.260	25
52000870	PG 16	0.591 - 0.709	15.0 - 18.0	0.945	1.024	0.295	1.379	25
52000880	PG 21	0.709 - 0.925	18.0 - 23.5	1.182	1.142	0.315	1.812	25
52000890	PG 29	0.906 - 1.221	23.0 - 31.0	1.615	1.300	0.315	2.285	10
52000900	PG 36	1.142 - 1.595	29.0 - 40.5	1.970	1.438	0.374	2.758	10
52000910	PG 42	1.339 - 1.773	34.0 - 45.0	2.245	1.497	0.394	3.073	5
52000920	PG 48	1.536 - 1.970	39.0 - 50.0	2.521	1.556	0.453	3.388	5