

Product Name: Facial Recognition Reader

Product Type: JFR-530

Features:

Features

Built-in dual cameras support multimodal video analysis technique. Very adequate to recognize faces under plural lights.

Supports offline recognition. No server or controller is required.

Supports liveness detection. Effectively reject hacking with photos and videos.

Effective reading range for EM is 6~10 cm. For Mifare is 3~5 cm.

Standard card format is EM. Mifare, HID 125Khz and others are optional.

10,000 user capacity for JFR-530.

130,000 history capacity.

Operation modes: card + facial recognition, pin code + facial recognition, card or pin code + facial recognition, facial recognition only.

RS485, RS232 and RS422 interfaces. TCP/IP is optional.

With a Wiegand output for upper controller/server.

With RTC.

With 2 RS232 contacts.

Reader ID is settable with keypad.

Programmable door closing delay time. Adjustable from 0 to 255 seconds. Alarm will be triggered after set delay time.

Built-in watch dog.

Built-in tamper switch and alarm.

With a detection loop for external detector.

Data is recorded during power failure.

Reader keeps on working when internet or server fails.

Authority can be set on reader or software.

With 24 settable time zones.

FAR <0.00001%

Accuracy rate 99.8%

Recognition speed <1 second.

Effective recognition range is 0.3~1 meter.

DC 12V 1A power.

4 * 4 backlit touch keypad.

Working temperature -20~50

Humidity 20%~90%


Dimension 143(L)*142.5(W)*38(H) mm

Specifications:

Installation Guidance and Using Instruction for JFR-530 Facial Recognition Reader

Notes:

1. Don't install the reader outside.
2. Don't install the reader under the direct sunlight.



Ordering Information:

Reference models:

Taiwan Jantek Electronics., Ltd.

Add: 6F-1, No. 1, Wuquan 1st. Rd., Xinzhuang District, TEL : 886-2-22991255

New Taipei City 24892, Taiwan, R.O.C.

FAX : 02-2299-1257 / 02-2299-7412

www.jantek.com.tw

Email : service@jantek.com.tw