

SXL | 美規厚肉 XLPE 照射汽車花線 (SAE Special Purpose - XLPE Wire)

產品說明 PRODUCT DESCRIPTION

*類別:  美規厚肉 XLPE 照射汽車花線

*導體: 符合 ASTM B3 規範軟銅絞線 Stranded copper conductor

*絕緣: XLPE 材質, 符合 SAE J1128 及 ROHS 規範 XLPE Insulation

*耐溫: -40~125℃

*多種顏色選擇 Any colors for customized



SXL 美規厚肉 XLPE 照射汽車花線, 適用於汽車、機車及各式運送工具之美規耐熱厚肉低壓 XLPE 絕緣花線。

SXL Heat-resistant low-tension XLPE wire with thick wall, suitable for automobiles, motorcycles, and other motor vehicles. SAEJ1128 compliant.

SXL | (SAE Special Purpose - XLPE Wire)

美規公稱 AWG	導體結構 mm X no.	絞合外徑 Overall Diameter	絕緣厚度		完成外徑		外被披覆 Material
			標準	最大	標準	最大	
20 AWG	0.32 mm / 7	1.0 mm	0.74 mm	0.52 mm	2.5 mm	2.8 mm	XLPE
20 AWG	0.19 mm / 19	1.0 mm	0.74 mm	0.52 mm	2.5 mm	2.8 mm	XLPE
18 AWG	0.23 mm / 19	1.2 mm	0.76 mm	0.53 mm	2.7 mm	3.0 mm	XLPE
16 AWG	0.29 mm / 19	1.5 mm	0.81 mm	0.57 mm	3.1 mm	3.4 mm	XLPE
14 AWG	0.36 mm / 19	1.8 mm	0.89 mm	0.62 mm	3.6 mm	3.9 mm	XLPE
12 AWG	0.45 mm / 19	2.3 mm	0.94 mm	0.66 mm	4.2 mm	4.6 mm	XLPE
10 AWG	0.58 mm / 19	3.0 mm	1.04 mm	0.73 mm	5.0 mm	5.3 mm	XLPE
8 AWG	0.45 mm / 50	3.7 mm	1.09 mm	0.76 mm	5.9 mm	6.2 mm	XLPE

大域科技股份有限公司

TA YU SCIENCE Co., Ltd



+886-3-329-8989



+886-3-329-7811



tayui@ms24.hinet.net



benson@tayui.com.tw



www.tayui.com.tw