

GXL | 美規一般 XLPE 汽車花線 (SAE General Purpose - XLPE Wire)

產品說明 PRODUCT DESCRIPTION

*類別:  美規一般 XLPE 汽車花線

*導體: 符合 ASTM B3 規範軟銅絞線 Stranded copper conductor

*絕緣: XLPE 材質, 符合 SAE J1128 及 ROHS 規範 XLPE Insulation

*耐溫: -40~125℃

*多種顏色選擇 Any colors for customized



GXL 美規一般 XLPE 汽車花線，適用於汽車、機車及各式運送工具之美規薄肉低壓絕緣花線。

GXL Heat-resistant low tension XLPE wire, suitable for automobiles, motorcycles, and other motor vehicles. SAEJ1128 compliant..

GXL | (SAE General Purpose - XLPE Wire)

美規公稱 AWG	導體結構 mm X no.	絞合外徑 Overall Diameter	絕緣厚度		完成外徑		外被披覆 Material
			標準	最大	標準	最大	
20 AWG	0.19 mm / 19	1.0 mm	0.58 mm	0.41 mm	2.15 mm	2.4 mm	XLPE
18 AWG	0.23 mm / 19	1.2 mm	0.58 mm	0.41 mm	2.4 mm	2.5 mm	XLPE
16 AWG	0.29 mm / 19	1.5 mm	0.58 mm	0.41 mm	2.7 mm	2.9 mm	XLPE
14 AWG	0.36 mm / 19	1.8 mm	0.58 mm	0.41 mm	3.0 mm	3.2 mm	XLPE
12 AWG	0.45 mm / 19	2.3 mm	0.66 mm	0.46 mm	3.6 mm	3.8 mm	XLPE
10 AWG	0.58 mm / 19	3.0 mm	0.79 mm	0.55 mm	4.5 mm	4.7 mm	XLPE
8 AWG	0.45 mm / 50	3.7 mm	0.94 mm	0.66 mm	5.6 mm	6.0 mm	XLPE

大域科技股份有限公司



+886-3-329-8989



tayui@ms24.hinet.net



www.tayui.com.tw

TA YU SCIENCE Co., Ltd



+886-3-329-7811



benson@tayui.com.tw