

FL2X-A | 歐規厚肉 XLPE 照射汽車花線 ISO Thick Wall XLPE Wire (Type A)

產品說明 PRODUCT DESCRIPTION

- *類別: ■ ■ 歐規厚肉 XLPE 照射汽車花線
- *導體: 符合 ISO 6722 規範軟銅絞線 Stranded copper conductor
- *絕緣: XLPE 材質, 符合 ISO 6722 及 ROHS 規範 XLPE Insulation
- *耐溫: -40~125℃
- *多種顏色選擇 Any colors for customized



FL2X-A 歐規厚肉 XLPE 照射汽車花線, 適用於汽車、機車及各式運送工具之耐熱厚肉低壓 XLPE 絕緣花線, 符合 ISO6722 規範。

FL2X-A is XLPE insulated, heat resistant, low tension wire with thick wall insulation, suitable for automobiles, motorcycles and other motor vehicles. ISO 6722 compliant.

FL2X-A | ISO Thick Wall XLPE Wire (Type A)

公稱截面積 mm ²	導體結構 mm X no.	絞合外徑 Overall Diameter	絕緣厚度		完成外徑	外被披覆 Material
			標準	最小	標準	
0.5 mm ²	0.19 mm / 19	1.0 mm	0.6 mm	0.48 mm	2.30 mm	XLPE
0.75 mm ²	0.23 mm / 19	1.2 mm	0.6 mm	0.48 mm	2.50 mm	XLPE
1.0 mm ²	0.26 mm / 19	1.3 mm	0.6 mm	0.48 mm	2.70 mm	XLPE
1.5 mm ²	0.32 mm / 19	1.7 mm	0.6 mm	0.48 mm	2.95 mm	XLPE
2.0 mm ²	0.36 mm / 19	2.0 mm	0.6 mm	0.48 mm	3.00 mm	XLPE
2.5 mm ²	0.41 mm / 19	2.1 mm	0.6 mm	0.48 mm	3.30 mm	XLPE

大域科技股份有限公司



+886-3-329-8989



tayui@ms24.hinet.net



www.tayui.com.tw

TA YU SCIENCE Co., Ltd



+886-3-329-7811



benson@tayui.com.tw