



NYLON-INSULATED CORD END TERMINALS (E SERIES)


MAXIMUM ELECTRIC CURRENT :














A.W.G.	26	24	22	20	18
AMP.	5.5	7	9	12	17

MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.

CONNECTOR MATERIAL : COPPER TUBE.

INSULATION MATERIAL : NYLON



WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION <small>inch mm</small>						FRENCH COLOR	GERMAN COLOR	DIN COLOR	CRIMPING TOOL
		F	L	W	B	D	C				
26 A.W.G. 0.25 mm ²	E 0206	.236 6.0	.409 10.4	.075 1.9	.173 4.4	.043 1.1	.031 0.8	VIOLET 	LIGHT BLUE 		K.S. MODEL LY-8-060 WITH DIE INDEX NO:0.25-0.75 OR WACO MODEL VARIOCRIMP 4
	E 0208	.315 8.0	.488 12.4								
24 A.W.G. 0.34 mm ²	E 0306	.236 6.0	.409 10.4	.075 1.9	.173 4.4	.043 1.1	.031 0.8	PINK 	TURQUOISE 		
	E 0308	.315 8.0	.488 12.4								
22 A.W.G. 0.5 mm ²	E 0505	.197 5.0	.433 11.0	.102 2.6	.236 6.0	.051 1.3	.039 1.0	WHITE 	ORANGE 	WHITE 	K.S. MODEL KST2000L WITH DIE INDEX NO:0.5 OR K.S. MODEL LY-8-060 WITH DIE INDEX NO:0.25-0.75 OR WACO MODEL VARIOCRIMP 4
	E 0506	.236 6.0	.472 12.0								
	E 0508	.315 8.0	.551 14.0								
	E 0510	.394 10.0	.630 16.0								
	E 0512	.472 12.0	.709 18.0								
20 A.W.G. 0.75 mm ²	E 7506	.236 6.0	.472 12.0	.110 2.8	.248 6.3	.059 1.5	.047 1.2	BLUE 	WHITE 	GREY 	K.S. MODEL KST2000L WITH DIE INDEX NO:0.75 OR K.S. MODEL LY-8-060 WITH DIE INDEX NO:0.25-0.75 OR WACO MODEL VARIOCRIMP 4
	E 7508	.315 8.0	.551 14.0								
	E 7508-L	.315 8.0	.571 14.5	.110 2.8	.260 6.3						
	E 7510	.394 10.0	.630 16.0								
	E 7512	.472 12.0	.709 18.0								
	E 7518	.709 18.0	.957 24.3								
18 A.W.G. 1.0 mm ²	E 1006	.236 6.0	.472 12.0	.118 3.0	.248 6.3	.067 1.7	.055 1.4	RED 	YELLOW 	RED 	K.S. MODEL KST2000L WITH DIE INDEX NO:1 OR K.S. MODEL LY-8-060 WITH DIE INDEX NO:1-1.5 OR WACO MODEL VARIOCRIMP 4
	E 1008	.315 8.0	.551 14.0								
	E 1008-L	.315 8.0	.571 14.5	.118 3.0	.248 6.3						
	E 1010	.394 10.0	.630 16.0								
	E 1012	.472 12.0	.709 18.0								
	E 1012-L	.472 12.0	.728 18.5								
	E 1018	.709 18.0	.957 24.3								

ALL LISTED



NYLON-INSULATED CORD END TERMINALS (E SERIES)


MAXIMUM ELECTRIC CURRENT :



















A.W.G.	16	14	12	10	8	6
AMP.	18	30	35	50	70	95

MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.

CONNECTOR MATERIAL : COPPER TUBE.

INSULATION MATERIAL : NYLON



WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION <small>inch mm</small>						FRENCH COLOR	GERMAN COLOR	DIN COLOR	CRIMPING TOOL				
		F	L	W	B	D	C								
16 A.W.G. 1.5 mm ²	E 1506	.236 6.0	.484 12.3	.138 3.5	.248 6.3			BLACK 	RED 	BLACK 	K.S. MODEL KST2000L WITH DIE INDEX NO:1.5 OR K.S. MODEL LY-8-060 WITH DIE INDEX NO:1-1.5 OR WACO MODEL VARIOCRIMP 4				
	E 1508	.315 8.0	.551 14.0	.138 3.5	.248 6.3										
	E 1508-L	.315 8.0	.571 14.5	.150 3.8	.256 6.5										
	E 1510	.394 10.0	.630 16.0	.138 3.5	.248 6.3										
	E 1512	.472 12.0	.709 18.0												
	E 1515	.591 15.0	.839 21.3												
	E 1518	.709 18.0	.945 24.0												
14 A.W.G. 2.5 mm ²	E 2508	.315 8.0	.551 15.0					GREY 	BLUE 	BLUE 	K.S. MODEL KST2000L WITH DIE INDEX NO:2.5 OR K.S. MODEL LY-8-060 WITH DIE INDEX NO:2.5 OR WACO MODEL VARIOCRIMP 4				
	E 2510	.394 10.0	.685 17.4												
	E 2512	.472 12.0	.709 18.0									.165 4.2	.291 7.4	.098 2.5	.087 2.2
	E 2518	.709 18.0	.945 24.0												
	E 2525	.984 25.0	1.276 32.4												
12 A.W.G. 4.0 mm ²	E 4009	.354 8.0	.646 16.4					ORANGE 	GREY 	GREY 	K.S. MODEL KST2000L LY-8-060 WITH DIE INDEX NO:4 OR WACO MODEL VARIOCRIMP 4				
	E 4010	.394 10.0	.669 17.0												
	E 4012	.472 12.0	.787 20.0												
	E 4018	.709 18.0	1.024 26.0												
10 A.W.G. 6.0 mm ²	E 6010	.394 10.0	.728 18.5					GREEN 	BLACK 	YELLOW 	K.S. MODEL KST2000M LY-8-060 OR WACO MODEL VARIOCRIMP 16 WITH DIE INDEX NO:6				
	E 6012	.472 12.0	.787 20.0									.248 6.3	.338 8.5	.154 3.9	.138 3.5
	E 6018	.709 18.0	1.024 26.0												
8 A.W.G. 10 mm ²	E 10-12	.472 12.0	.886 22.0					BROWN 	IVORY 	RED 	K.S. MODEL KST2000M OR WACO MODEL VARIOCRIMP 16 WITH DIE INDEX NO:10				
	E 10-15	.591 15.0	.929 23.6									.299 7.6	.346 8.8	.193 4.9	.177 4.5
	E 10-18	.709 18.0	1.102 28.0												
6 A.W.G. 16 mm ²	E 16-12	.472 12.0	.945 24.0					IVORY 	GREEN 	BLUE 	K.S. MODEL KST2000M OR WACO MODEL VARIOCRIMP 16 WITH DIE INDEX NO:16				
	E 16-18	.709 18.0	1.102 28.0									.346 8.8	.394 10.0	.244 6.2	.228 5.8

ALL LISTED



NYLON-INSULATED CORD END TERMINALS (E SERIES)


MAXIMUM ELECTRIC CURRENT :
















A.W.G.	4	2	1/0	2/0	3/0
AMP.	125	170	230	265	310

MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.

CONNECTOR MATERIAL : COPPER TUBE.

INSULATION MATERIAL : NYLON



WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION <small>inch mm</small>						FRENCH COLOR	GERMAN COLOR	DIN COLOR	CRIMPING TOOL
		F	L	W	B	D	C				
4 A.W.G. 25 mm ²	E 25-12	.472 12.0	.945 24.0	.441 11.2	.472 12.0	.303 7.7	.287 7.3	BLACK 	BROWN 	YELLOW 	K.S. MODEL KSTP-325-B WITH DIE INDEX NO:KC-25
	E 25-15	.591 15.0	1.063 27.0								
	E 25-16	.630 16.0	1.102 28.0								
	E 25-18	.709 18.0	1.181 30.0								
	E 25-22	.886 22.0	1.417 36.0								
	E 25-25	.984 25.0	1.457 37.0								
2 A.W.G. 35 mm ²	E 35-16	.630 16.0	1.181 30.0	.500 12.7	.551 14.0	.343 8.7	.327 8.3	RED 	BEIGE 	RED 	K.S. MODEL KSTP-325-B WITH DIE INDEX NO:KC-35
	E 35-18	.709 18.0	1.181 30.0								
	E 35-22	.866 22.0	1.147 36.0								
	E 35-25	.984 25.0	1.535 39.0								
1/0 A.W.G. 50 mm ²	E 50-12	.472 12.0	1.102 28.0	.591 15.0	.630 16.0	.429 10.9	.406 10.3	BLUE 	OLIVE 	BLUE 	K.S. MODEL KSTP-325-B WITH DIE INDEX NO:KC-50
	E 50-16	.630 16.0	1.260 32.0								
	E 50-20	.787 20.0	1.417 36.0								
	E 50-22	.866 22.0	1.496 38.0								
	E 50-25	.984 25.0	1.575 40.0								
	E 50-30	1.181 30.0	1.811 46.0								
2/0 A.W.G. 70 mm ²	E 70-20	.787 20.0	1.457 37.0	.630 16.0	.669 17.0	.563 14.3	.531 13.5	YELLOW 	YELLOW 	YELLOW 	K.S. MODEL KSTP-325-B WITH DIE INDEX NO:KC-70
	E 70-25	.984 25.0	1.654 42.0								
	E 70-27	1.063 27.0	1.732 44.0								
3/0 A.W.G. 95 mm ²	E 95-25	.984 25.0	1.732 44.0	.728 18.5	.748 19.0	.614 15.6	.583 14.8	RED 	RED 	RED 	K.S. MODEL KSTP-325-B WITH DIE INDEX NO:KC-95
	E 95-30	1.181 30.0	1.953 49.6								

ALL LISTED



NYLON-INSULATED CORD END TERMINALS (E SERIES)


MAXIMUM ELECTRIC CURRENT :

A.W.G.	4/0	250	300
AMP.	360	405	445

MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.

CONNECTOR MATERIAL : COPPER TUBE.

INSULATION MATERIAL : NYLON



WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION <small>inch mm</small>						FRENCH COLOR	GERMAN COLOR	DIN COLOR	CRIMPING TOOL
		F	L	W	B	D	C				
4/0 A.W.G. 120 mm ²	E 120-27	1.063 27.0	1.874 47.6	.799 20.3	.811 20.6	.697 17.7	.657 16.7	BLUE ●	BLUE ●	BLUE ●	K.S. MODEL KSTP-325-B WITH DIE INDEX NO:KC-120
	E 120-30	1.181 30.0	2.008 51.0								
	E 120-32	1.260 32.0	2.071 52.6								
	E 120-34	1.339 34.0	2.150 54.6								
250/300 MCM 150 mm ²	E 150-25	.984 25.0	1.992 50.6	.921 23.4	1.008 25.6	.811 20.6	.772 19.6	YELLOW ●	YELLOW ●	YELLOW ●	K.S. MODEL KSTP-325-B WITH DIE INDEX NO:KC-150
	E 150-27	1.063 27.0	2.071 52.6								
	E 150-32	1.260 32.0	2.268 57.6								
	E 150-38	1.496 38.0	2.504 63.6								

ALL LISTED