

Product Name: Multi Door Access

Control System

Product Type: JST-420R

#### Features:

- . PC on line through the software, when PC or internet shut down, the Controller can work alone
- . To Control 16 x RS485 interface reader
- . Support 190,000 history transaction or alarm data
- . Card capacity is 31,000 cards, each card can be set 4 digit personal ID
- . Network communication via RS232/RS485 or TCP/IP (optional)
- . Built-in Watch Dog feature
- . Built-in clock and calendar
- . Auto detect Reader status
- . 8 Programmable time zones, 3 schedules per time zone
- . Door open mode: Card only, Card with Keypad, Card or Keypad, Opening or Inhibit access
- . Built-in buzzer
- . To control I/O board (JRB series) for remote control
- . Programmable door release time or alarm time
- . Controller ID is programmable through internal Keypad and LCD display
- . System setting and history data is protected even after power failure,
- . With one reset button to reset the controller
- . With ISP function to update the program of controller

- . With one emergency dry contact when fire is occurrence, controller willtrigger all door locks open
- . With 4 LED, two LED indicate the communication status between Controller & PC, two LED indicate the communication status between Controller and Reader

Specifications:

. Power: 75W Switching Power (UL, CB, CCC approved)

Input: AC 100~240VAC

Output: 12VDC

. Keypad: 4 x 4 keys


. LCD: 16 x 2 Character

. Operating Temperature:0 ~60


Humidity:20%~90% RH

. Dimension:290 x 240 x 78 mm


# A: JST-420 System Configuration (TCP/IP)




## B: JST-420 System Configuration (RS-485)



# C: JST-420 System Configuration (RS-485)



### JST-420R & RS-485 Reader System Diagram (RS-485)



#### Ordering Information:

#### Reference models:

Taiwan Jantek Electronics., Ltd. www.jantek.com.tw Add:6F-1, No. 1, Wuquan 1St.Rd., Xinzhuang District, TEL: 886-2-22991255

New Taipei City 24892, Taiwan, R.O.C.