

Product Name: Face recognition and palm prints reader

Product Type: JFR-650

Features:

Features

Face recognition and palm prints reader.

User capacity is 5,000.

History record capacity is 1,000,000.

Operation modes: card only, card + pin code, palm print only, palm print + card number, card number only, card number + pin code, face recognition 1:N.

Recognition speed is less than 500ms.

Supports liveness detection.

Effective reading range for faces is 50~220 cm.

Effective reading range for live faces is 50~130 cm.

Can recognize users with face masks. (Settable)

With voice prompts.

$FRR \leq 0.01\%$

$FAR \leq 0.001\%$

Specifications:

Specification

1 reed switch contact.

1 relay output.

1 push button contact.

1 Wiegand output supports Wiegand 26/34/42 bit for separate controller.

LINUX OS

2 high resolution color cameras

1 LED bright fill light (automatically adjust to ambient lights)

1 infrared fill light

4.3 inch touch screen

TCP/IP communication

Dimension 190(L) × 90(W) × 26(H) mm

Working voltage DC12V ± 10%

Supply voltage DC 12V , 2A

Working temperature - 20 ~ 50

Working humidity 10% ~ 85%

Ordering Information:

Reference models:

JFR-530Facial Recognition Reader

JFR-300Embedded IR Facial Recognition

Taiwan Jantek Electronics., Ltd.

www.jantek.com.tw

Add:6F-1, No. 1, Wuquan 1St.Rd.,Xinzhuang District, TEL : 886-2-22991255

New Taipei City 24892,Taiwan, R.O.C.

FAX : 02-2299-1257 / 02-2299-7412

Email : service@jantek.com.tw