



VINYL-INSULATED SPADE TERMINALS

MAXIMUM ELECTRIC CURRENT :


A.W.G.	22	20	18	16	14
AMP.	9	12	17	18	30

MAXIMUM ELECTRICAL RATING : 75°C 600 VOLTS MAX.

INSULATION MATERIAL : VINYL

INSULATION COLOR :

22-16 A.W.G.: RED 16-14 A.W.G.: BLUE

TERMINAL MATERIAL : COPPER


WIRE RANGE A.W.G. mm ²	ITEM NO.		STUD SIZE	DIMENSION <small>inch mm</small>								CRIMPING TOOL	Q'TY BOX
	BRAZED SEAM	BRAZED SEAM		d2	W	F	L	E	D	d1	T		
22-16 A.W.G. 0.5-1.5 mm ²	SVB1-3.2	VF1-3.2Y	#4	.126 3.2	.224 5.7							IZUMI MODEL 34 WITH DIE INDEX COLOR:RED OR K.S. MODEL KST2000A HRI-126 WITH DIE INDEX COLOR:RED	1000
	SVBS1-3.7	VF1-3.7YS	#6	.146 3.7	.224 5.7								1000
	SVBL1-3.7	VF1-3.7YL	#6	.146 3.7	.252 6.4	.256 6.5	.827 21.0						1000
	SVBLL1-3.7	VF1-3.7YLL	#6	.146 3.7	.283 7.2								1000
	SVBS1-4	VF1-4YS	#8	.169 4.3	.252 6.4								1000
	SVBM1-4	VF1-4YM	#8	.169 4.3	.283 7.2			.394 10.0	.157 4.0	.067 1.7	.030 0.75		1000
	SVBL1-4	VF1-4YL	#8	.169 4.3	.319 8.1								1000
	SVBS1-5	VF1-5YS	#10	.209 5.3	.319 8.1	.256 6.5	.827 21.0						1000
	SVBL1-5	VF1-5YL	#10	.209 5.3	.374 9.5								1000
	SVBS1-6	VF1-6YS	1/4	.252 6.4	.374 9.5								1000
	SVBL1-6	VF1-6Y	1/4	.252 6.4	.472 12.0	.433 11.0	1.063 27.0						1000
16-14 A.W.G. 1.5-2.5 mm ²	SVB2-3.2	VF2-3.2Y	#4	.126 3.2	.224 5.7							IZUMI MODEL 34 WITH DIE INDEX COLOR:BLUE OR K.S. MODEL KST2000A HRI-126 WITH DIE INDEX COLOR:BLUE	1000
	SVBS2-3.7	VF2-3.7YS	#6	.146 3.7	.224 5.7								1000
	SVBL2-3.7	VF2-3.7YL	#6	.146 3.7	.236 6.0	.256 6.5	.827 21.0						1000
	SVBLL2-3.7	VF2-3.7YLL	#6	.146 3.7	.283 7.2								1000
	SVBS2-4	VF2-4YS	#8	.169 4.3	.252 6.4								1000
	SVBM2-4	VF2-4YM	#8	.169 4.3	.283 7.2			.394 10.0	.177 4.5	.091 2.3	.031 0.8		1000
	SVBL2-4	VF2-4YL	#8	.169 4.3	.311 7.9								1000
	SVBS2-5	VF2-5YS	#10	.209 5.3	.311 7.9	.256 6.5	.827 21.0						1000
	SVBL2-5	VF2-5YL	#10	.209 5.3	.366 9.3								1000
	SVBS2-6	VF2-6YS	1/4	.252 6.4	.366 9.3								1000
	SVBL2-6	VF2-6YL	1/4	.252 6.4	.472 12.0	.433 11.0	1.063 27.0						1000



ALL LISTED

*: ADDITIONAL CERTIFIED



VINYL-INSULATED SPADE TERMINALS

MAXIMUM ELECTRIC CURRENT :

A.W.G.	14	12	10
AMP.	30	35	50


MAXIMUM ELECTRICAL RATING : 75°C 600 VOLTS MAX.

INSULATION MATERIAL : VINYL

INSULATION COLOR :

14-12 A.W.G.: BLACK 12-10 A.W.G.: YELLOW

TERMINAL MATERIAL : COPPER



WIRE RANGE A.W.G. mm ²	ITEM NO.		STUD SIZE		DIMENSION <small>inch mm</small>							CRIMPING TOOL	Q'TY BOX
	BRAZED SEAM	BRAZED SEAM	d2		W	F	L	E	D	d1	T		
14-12 A.W.G. 2.5-4 mm ²	SVB3-3.7	VF3-3.7Y	#6	.146 3.7								IZUMI MODEL 214 WITH DIE INDEX COLOR:BLACK OR K.S. MODEL KST2000A HRI-126 WITH DIE INDEX COLOR:BLACK	1000
	SVB3-4	VF3-4Y	#8	.169 4.3	.315 8.0	.276 7.0	.996 25.3						1000
	SVB3-5	VF3-5Y	#10	.209 5.3				.512 13.0	.248 6.3	.118 3.0	.039 1.0		1000
	SVB3-6	VF3-6Y	1/4	.252 6.4	.472 12.0	.358 9.1	1.122 28.5						1000
12-10 A.W.G. 4-6 mm ²	SVBS5-3.7	VF5-3.7YS	#6	.146 3.7	.283 7.2	.295 7.5	.961 24.4					IZUMI MODEL 5 WITH DIE INDEX COLOR:YELLOW OR K.S. MODEL KST2000A HRI-126 WITH DIE INDEX COLOR:YELLOW	500
	SVB5-3.7	VF5-3.7Y	#6	.146 3.7	.327 8.3	.276 7.0	1.004 25.5						500
	SVBSS5-4	VF5-4YSS	#8	.169 4.3	.283 7.2	.295 7.5	.961 24.4						500
	SVBS5-4	VF5-4YS	#8	.169 4.3	.327 8.3								500
	SVBL5-4	VF5-4YL	#8	.169 4.3		.276 7.0	1.004 25.5	.512 13.0	.252 6.4	.134 3.4	.039 1.0		500
	SVB5-5	VF5-5Y	#10	.209 5.3	.354 9.0								500
	SVBS5-6	VF5-6YS	1/4	.252 6.4									500
	SVBL5-6	VF5-6YL	1/4	.252 6.4	.472 12.0	.472 12.0	1.240 31.5						500
	SVB5-8	VF5-8Y	5/16	.331 8.4	.551 14.0	.413 10.5	1.201 30.5						500



ALL LISTED

*: ADDITIONAL CERTIFIED