



Product Name: TCPIP Converter

Product Type: JTC-200

Features:

TCP/IP Converter

Specifications:

Hardware

CPU : 32 bit CPU, 80MHz

Memory : 4MB FLASH, 8MB SDRAM

Connector Type : DB9 (Male)/ RJ-45

Watch Dog : Support watch Dog, system never hang

Interface

Ethernet : 10/100Base-T (Auto Detecting)

Serial : RS-232/485/422 ,half/full duplex

No. of serial Port : 1

Signals : RS-232: TxD, RxD, RTS, CTS, GND

RS-485 2 wire: A+/B- RS-422 4 wire: T+/T-, R+/R-

Baud rate : 1200 bps ~115.2Kbps

Configuration

Parity Check : None,even,odd,Mark,Space

Data bits : 5, 6, 7, 8

Stop bits : 1, 2

Flow Control : RTS/CTS

Supported OS

Windows XP, Windows 2000, Windows NT, Windows95/98 ME, Vista

Protocol

TCP, IP, UDP, ARP, DHCP, ICMP、HTTP、DDNS

Management

Support TCP/UDP Server/Client mode

User name & password protected for web management

Built-in Http server for set up and remote management via any browser easily

Power requirement & Environment

Power requirement : DC 9V~24V , Max. 600mA

Operation Temp. : 0-55

Operation Humidity : 5 - 95%RH

Storage Temp : -20-85

Size : 120 x 75 x 25 mm (W x L x H)

Surge protection : Serial port 15 KV ESD


Magnetic protected : Ethernet port 1.5 KV

Approval : FCC B, CE B

Ordering Information:

重要!	讀取卡片種類	通訊介面	顯示幕文字
確定訂購規格與業務人員洽詢！ 可能有所變動，如需進一步，請與業務人員洽詢！	E=EM	T=TCP/IP	E=英文字
	N=TEMIC鎖碼	R=RS232 RS485 RS422	C=中文字
	M=Mifare	---	---
	T=TI	---	---
	H=HID	---	---
	F=Felica	---	---

- 型號標準為：型號-讀取卡片種類(E/N/M/T/H/F)-通訊介面(T/R)-顯示幕文字(E/C)
- 讀取卡片種類為：E=EM，N=TEMIC鎖碼，M=Mifare，T=TI，H=HID，F=Felica
- 通訊介面為：T=TCP/IP，R=RS232, RS485, RS422
- 顯示幕文字為：E=英文字，C=中文字
- 例：如訂購 PR-80C TCP/IP介面的Mifare中文顯示讀卡機，則訂貨型號註明：PR-80C-M-T-C



Reference models:

Taiwan Jantek Electronics., Ltd.

Add:6F-1, No. 1, Wuquan 1St.Rd.,Xinzhuang District, TEL : 886-2-22991255

New Taipei City 24892,Taiwan, R.O.C.

FAX : 02-2299-1257 / 02-2299-7412

www.jantek.com.tw

Email : service@jantek.com.tw