

MAP® POWER CABLE SVT.VDE.PSE

歐規 日規電源線

產品說明 PRODUCT DESCRIPTION

*軟裸銅絞線 Bare stranded copper conductor

*聚氯乙烯絕緣 Insulation

*額定溫度 60°C 75°C 105°C Rated temperature 60°C 75°C 105°C

*額定電壓 300 伏特 Rated voltage:300V

*防水聚氯乙烯披覆 Water-proof PVC Jacket

*耐油.耐刻痕.Oil Resistance.Abrasion.

*SJTO 抗油性佳,SJTW-A 適合惡劣環境 SJTO oil-res trait,SJTO for outdoor use





歐規 VDE POWER CABLE

適用於小型室內器具.家電產品之電源配線。

Suitable for indoor small electrical instruments.

MAP® 歐規 VDE POWER CABLE

VDE 認證	結構	導體結構	絕緣厚度	披覆厚度	完成外徑
MODEL	MM ² X C	NO.X MM	INS THK	JAC THK	OVERALL DIA
H03VVH2-F	0.75mm ² x 2C	24/0.2	0.5 mm	0.6 mm	3.5mm x 5.7mm
H03VV-F	0.75mm ² x 2C	24/0.2	0.5 mm	0.6 mm	5.5 mm
H03VV-F	0.75mm ² x 3C	24/0.2	0.5 mm	0.6 mm	6.0 mm
H05VVH2-F	0.75mm ² x 2C	24/0.2	0.6 mm	0.6 mm	4.0mm x 6.4mm
H05VV-F	0.75mm ² x 2C	24/0.2	0.6 mm	0.6 mm	6.5 mm
H05VV-F	1.0 mm ² x 2C	32/0.2	0.6 mm	0.6 mm	6.7 mm
H05VV-F	0.75mm ² x 3C	24/0.2	0.6 mm	0.6 mm	6.8 mm
H05VV-F	1.0mm ² x 3C	32/0.2	0.6 mm	0.6 mm	7.0 mm



日規 PSE **JIS C3306** POWER CABLE

適用於電器設備/燈具/喇叭廣播設備等。

Suitable for the electrical instruments/lighting/speaker broadcast.

MAP® 日規 PSE JIS POWER CABLE

PSE 認證	結構	導體結構	絕緣厚度	披覆厚度	完成外徑
MODEL	MM ² X C	NO.X MM	INS THK	JAC THK	OVERALL DIA
VFF/HVFF	0.75mm ² x 2C	30/0.18	0.8 mm	-----	2.7mm x 5.4mm
VFF/HVFF	1.25mm ² x 2C	50/0.18	0.8 mm	-----	3.1mm x 6.2mm
VFF/HVFF	2.0mm ² x 2C	37/0.26	0.8 mm	-----	3.4mm x 6.8mm
VCTF/HVCTF	0.75mm ² x 2C	30/0.18	0.6 mm	1.0 mm	6.6mm
VCTF/HVCTF	1.25mm ² x 2C	50/0.18	0.6 mm	1.0 mm	7.4mm
VCTF/HVCTF	2.0mm ² x 2C	37/0.26	0.6 mm	1.0 mm	8.0mm
VCTF/HVCTF	0.75mm ² x 3C	30/0.18	0.6 mm	1.0 mm	7.0mm

PSE 認證	結構	導體結構	絕緣厚度	披覆厚度	完成外徑
MODEL	MM ² X C	NO.X MM	INS THK	JAC THK	OVERALL DIA
VCTF/HVCTF	1.25mm ² x 3C	50/0.18	0.6 mm	1.0 mm	7.8mm
VCTF/HVFCTF	2.0mm ² x 3C	37/0.26	0.6 mm	1.0 mm	8.5mm
VCTFK/HVCTFK	0.75mm ² x 2C	30/0.18	0.6 mm	1.0 mm	4.3mm x6.6mm
VCTFK/HVCTFK	1.25mm ² x 2C	50/0.18	0.6 mm	1.0 mm	4.7mm x 7.4mm
VCTFK/HVCTFK	2.0mm ² x 2C	37/0.26	0.6 mm	1.0 mm	5.0mm x 8.0mm

大域科技股份有限公司

TA YU SCIENCE Co., Ltd

 +886-3-329-8989

 +886-3-329-7811

 tayui@ms24.hinet.net

 benson@tayui.com.tw

 www.tayui.com.tw