



尼龍剖開與不剖開浪管

型號 Item NO.		內徑	外徑	包裝
剖開	不剖開	AØ	BØ	Packing
CRP-05P	CRP-05	5.4	7.8	300M
CRP-07P	CRP-07	7.4	10.2	
CRP-10P	CRP-10	10.7	14.1	200M
CRP-13P	CRP-13	13.2	17.5	
CRP-15P	CRP-15	15.0	19.5	100M
CRP-19P	CRP-19	19.3	23.8	
CRP-22P	CRP-22	22.2	27.0	
CRP-25P	CRP-25	25.0	30.0	50M
CRP-28P	CRP-28	28.0	34.0	
CRP-32P	CRP-32	32.0	38.0	

材質:Pa66 黑色
用途:一般電線包紮及汽車配線用



歐規尼龍軟管

型號 Item NO.	規格 size	適用軟管	內徑	外徑	包裝 Packing
			A	B	
CP-07	1/4"	AD-10	6.5	10.0	100M
CP-09	5/16"	AD-13	9.6	13.0	
CP-11	3/8"	AD-15.8	12.0	15.8	
CP-13.5		AD-18.5	14.0	18.5	
CP-16	1/2"	AD-21.2	16.2	21.2	
CP-21	3/4"	AD-28.5	21.9	28.5	50M
CP-29	1"	AD-34.5	27.6	34.5	
CP-36	1-1/4"	AD-42.5	36.0	42.5	25M
CP-42		AD-48			
CP-48	2"	AD-54.5	47.0	54.5	

材質:尼龍Pa66製成.耐溫105°C
用途:一般電線保護.機械配線整齊美觀



防水尼龍浪管接頭

型號 Item NO.	適用軟管	螺紋外徑	螺紋長度	包裝 Packing
		(mm)	(mm)	
PF1/4	AD-10.0	13.1	9.0	50Pcs
PF3/8	AD-13.0	16.6	15.0	
PF1/2	AD-15.8	20.9	15.0	
PF1/2	AD-18.5	20.9	15.0	
PF1/2	AD-21.2	20.9	15.0	
PF3/4		26.4	15.0	
PF1/2	AD-25.0	20.9	15.0	
PF3/4		26.4	15.0	
PF 1	AD-34.5	33.2	15.0	20Pcs
PF1-1/4	AD-42.5	41.9	15.0	10Pcs

材質:尼龍Pa66製成
用途:浪管連接控制盒或箱體用



歐規尼龍軟管固定座

型號 Item NO.	規格 size	適用軟管	寬度	高度	包裝 Packing
			L(mm)	H(mm)	
PU-07		AD-10	20	23	100 Pcs
PU-09		AD-13	23	26	
PU-11	3/8"	AD-15.8	26	28	
PU-13.5		AD-18.5	28	30	
PU-16	1/2"	AD-21.2	31	33	
PU-21	3/4"	AD-28.5	38	42	50Pcs
PU-29	1"	AD-34.5	43	52	
PU-36	1-1/4"	AD-42.5	52	62	10Pcs
PU-42		AD-48			
PU-48	2"	AD-54.5	64	72	

材質:尼龍Pa66製成
用途:可以固定軟管,操作方便



尼龍軟管固定頭

型號 Item NO.	規格 size	適用軟管	內徑	外徑	包裝 Packing
			A	B	
PG-7	1/4"	AD-10	9	12.3	50Pcs
PG-9	5/16"	AD-13	11.2	15.2	
PG-11	3/8"	AD-15.8	12.0	20.4	
PG-13.5		AD-18.5		18.5	
PG-16	1/2"	AD-21.2	17.5	22.5	
PG-21	3/4"	AD-28.5	24.0	28.5	
PG-29	1"	AD-34.5	26.5	37.0	25Pcs
PG-36	1-1/4"	AD-42.5	36.0	47.0	10Pcs
PG-42		AD-48			
PG-48	2"	AD-54.5	46.0	59.0	

材質:尼龍Pa66製成
用途:歐規尼龍軟管連接控制盒用



尼龍軟管彎接頭

型號 Item NO.	規格 size	適用軟管	內徑	外徑	包裝 Packing
			A	B	
PG-7L	1/4"	AD-10	9	12.3	50Pcs
PG-9L	5/16"	AD-13	11.2	15.2	
PG-11L	3/8"	AD-15.8	12.0	20.4	
PG-13.5L		AD-18.5		18.5	
PG-16L	1/2"	AD-21.2	17.5	22.5	
PG-21L	3/4"	AD-28.5	24.0	28.5	25Pcs
PG-29L	1"	AD-34.5	26.5	37.0	
PG-36L	1-1/4"	AD-42.5	36.0	47.0	20Pcs
PG-42L		AD-48			10Pcs
PG-48L	2"	AD-54.5	46.0	59.0	

材質:尼龍Pa66製成
用途:機械本體與線路接合固定



尼龍軟管快速直接頭(PG 牙)

型號 Item NO.	規格 size	適用軟管 Accommodated Pipes	通徑 鐵板孔		包裝 Packing
			A	B	
PG-7	1/4"	AD-10	9	12.0	100 Pcs
PG-9	5/16"	AD-13	11.2	15.8	
PG-11	3/8"	AD-15.8	12.0	18.5	50Pcs
PG-13.5		AD-18.5	14.0	20.4	
PG-16	1/2"	AD-21.2	17.5	22.5	
PG-21	3/4"	AD-28.5	24.0	28.5	
PG-29	1"	AD-34.5	26.5	34.5	25Pcs
PG-36	1-1/4"	AD-42.5	36.0	47.0	10Pcs
PG-42		AD-48			
PG-48	1-1/4"	AD-54.5	46.0	54.5	

材質:尼龍Pa66製成
用途:歐規尼龍軟管連接控制盒用



尼龍軟管快速直接頭(PF 牙)

型號 Item NO.	規格 size	適用軟管 Accmmodated Pipes	通徑 鐵板孔		包裝 Packing
			A	B	
PFG-02	1/4"	AD-10	9	12.0	100
PFG-2.5	5/16"	AD-13	11.2	15.0	Pcs
PFG-03	3/8"	AD-15.8	11.4	20.7	50Pcs
PFG-04	1/2"	AD-18.5	17.5	20.7	
PFG-06	3/4"	AD-21.2	24.0	26.5	
PFG-10	1"	AD-28.5	26.5	33.5	25Pcs
PFG-12	1-1/4"	AD-34.5	36.0	42.0	10Pcs
PFG-20	2"	AD-42.5	46.0	54.0	

材質:尼龍Pa66製成
用途:歐規尼龍軟管連接控制盒用



尼龍軟管快速直接頭(M 牙)

型號 Item NO.	規格 size	適用軟管 Accmmodated Pipes	螺紋外徑 B(mm)	通徑 A(mm)	包裝 Packing
PMG-12	1/4"	AD-10	12	9	50Pcs
PMG-16S	5/16"	AD-13	16	11.6	
PMG-16	3/8"	AD-15.8	16	12	
PMG-20S	3/8"	AD-15.8	20	15	
PMG-20	1/2"	AD-21.2	20	15	
PMG-25S	1/2"	AD-21.2	25	16	
PMG-25	3/4"	AD-28.5	25	19.5	
PMG-32	1"	AD-34.5	32	27	25Pcs
PMG-40	1-1/4"	AD-42.5	40	35	10Pcs
PMG-50		AD-48	50	44	
PMG-63	2"	AD-54.5	63	55	

材質:尼龍Pa66製成
用途:歐規尼龍軟管連接控制盒用



尼龍軟管快速彎接頭

型號 Item NO.	規格 size	適用軟管 Accmmodated Pipes	通徑		包裝 Packing
			A	B	
PFL-02	1/4"	AD-10	9	12.0	50Pcs
PFL-2.5	3/8"	AD-13	11.2	15.0	
PFL-03	1/2"	AD-15.8	11.4	20.7	
PFL-04	1/2"	AD-18.5	17.5	20.7	
PFL-06	1/2"	AD-21.2	24.0	26.5	25Pcs
PFL-10	3/4"	AD-28.5	26.5	33.5	
PFL-12	1"	AD-34.5	36.0	42.0	10Pcs
PFL-20	2"	AD-42.5	46.0	54.0	

材質:尼龍Pa66製成
用途:歐規尼龍軟管連接控制盒用



尼龍軟管快速彎接頭(PG 牙)

型號 Item NO.	適用軟管 Accommodated Pipes	螺紋外徑	螺紋內徑	螺紋長度
		B	A	C
PGL-07	AD-10	12.5	9	10
PGL-09	AD-13	15.2	11.6	10
PGL-11	AD-15.8	18.6	14.5	10
PGL-13.5	AD-18.5	20.4	16	11
PGL-16	AD-21.2	22.5	17.5	13
PGL-21	AD-28.5	28.3	23	13
PGL-29	AD-34.5	37	30	14.5
PGL-36	AD-42.5	47	38	16
PGL-48	AD-48	60	52	16

材質:尼龍製成。以上尺寸單位為m/m(公厘)。
用途:歐規尼龍軟管連接控制盒用。



尼龍軟管快速彎接頭(M 牙)

型號 Item NO.	適用軟管 Accommodated Pipes	螺紋外徑	螺紋內徑	螺紋長度
		B	A	C
MGL-12	AD-10	12	9.0	10
MGL-16S	AD-13	16	11.6	10
MGL-16	AD-15.8	16	12	10
MGL-20S	AD-15.8	20	15	10
MGL-20	AD-21.2	20	15	13
MGL-25S	AD-21.2	25	16	13
MGL-25	AD-28.5	25	19.5	13
MGL-32	AD-34.5	32	27	14.5
MGL-40	AD-42.5	40	35	15
MGL-50	AD-48	50	44	16
MGL-63	AD-54.5	63	55	16

材質:尼龍製成。以上尺寸單位為m/m(公厘)。
用途:歐規尼龍軟管連接控制盒用。