



Product Name: RS485/RS422 to USB
CONVERTER

Product Type: ATC-105U

Features:

■ Features:(ATC-105U)

- ATC-105U needs no any external power resource and conformed to the USB/RS-422 and RS-485 standard and policies.

Specifications:

- Support OS: Windows95/98/2000/xp/Windows vista/Windows 7
- Standard: USB V2.0、EIA RS-485、RS-422
- USB Signal: VCC、DATA+、DATA-、GND、FG
- RS-485 Signal: T+、T-
- RS-422 Signal: T+、T-、R+、R-
- LED: Power、RX、TX LED indicate
- Baud Rate:
300~115200 bps, automatic detect the serial port speed.
- Communication Effective Length:
RS-485 → 1.2KM / RS-422 → 1.2KM
- Load Ability: In point to multi-points each
converter can connects 256 units of RS-422
or RS-485 interface equipments.
- Surge Protection: 15 KV ESD for all signals
- Dimensions: 450 (L) X 35 (W) X 18 (H) mm
- Power: USB 25mA ,DC5V
- Operation Temperature: -40 ° C ~ 85 ° C

■ Humidity: 10% ~ 95% RH

Ordering Information:

Reference models:

Taiwan Jantek Electronics., Ltd.

www.jantek.com.tw

Add:6F-1, No. 1, Wuquan 1St.Rd.,Xinzhuang District, TEL : 886-2-22991255

New Taipei City 24892, Taiwan, R.O.C.

FAX : 02-2299-1257 / 02-2299-7412

Email : service@jantek.com.tw