

VINYL-INSULATED BLADE TERMINALS

 MAXIMUM ELECTRIC CURRENT:

 A.W.G.
 26
 24
 22
 20
 18
 16
 14
 12
 10

 AMP.
 5.5
 7
 9
 12
 17
 18
 30
 35
 50


 MAXIMUM ELECTRICAL RATING: 75°C 600 VOLTS MAX.

INSULATION MATERIAL: VINYL

INSULATION COLOR:

26-22 A.W.G.: YELLOW 12-10 A.W.G.: YELLOW 22-16 A.W.G.: RED 16-14 A.W.G.: BULE

TERMINAL MATERIAL: COPPER



WIRE RANGE A.W.G. mm²	ITEM NO.		DIMENSION inch							CRIMPING	Q'TY
	BRAZED SEAM	BUTTED SEAM	W	F	L	Е	D	d1	Т	TOOL	вох
26-22 A.W.G. 0.5-1.5 mm ²	DBVB0.5-8	© DBV0.5-8	.059 1.5	.315 8.0	.630 16.0	.315 8.0	.087	.039 1.0	.020 0.5	K.S. MODEL LY8-067 WITH DIE INDEX NO:0.5	1000
22-16 A.W.G. 0.5-1.5 mm ²	DBVB1-9	DBV1-9	.110 2.8	.354 9.0	.740 18.8	.394	.157 4.0	.067 1.7	.030 075	IZUMI MODEL 34 WITH DIE INDEX COLOR:RED OR K.S. MODEL KST2000A HRI-126 WITH DIE INDEX COLOR:RED	1000
	DBVB1-10	DBV1-10	.091	.394 10.0	.780 19.8						1000
	DBVB1-11	DBV1-11	.118 3.0	.433 11.0	.819 20.8						1000
	DBVB1-13	DBV1-13	.118 3.0	.512 13.0	.898 22.8						1000
	DBVB1-14	DBV1-14	.118 3.0	.551 14.0	.937 23.8						1000
	DBVB1-18	DBV1-18	.087 2.2	.709 18.0	4 00 4						1000
	DBVBS1-18	DBVS1-18	.079 2.0		1.094 27.8						1000
16-14 A.W.G. 1.5-2.5 mm²	DBVB2-9	DBV2-9	.110 2.8	.354 9.0 .394 10.0	.740 18.8	3 .394 10.0	.177 4.5	.091 2.3	.031 0.8	IZUMI MODEL 34 WITH DIE INDEX COLOR:BLUE OR K.S. MODEL KST2000A HRI-126 WITH DIE INDEX COLOR:BLUE	1000
	DBVB2-10	DBV2-10	.094 2.4		.780 19.8						1000
	DBVB2-13	DBV2-13	.094 2.4	.512 13.0	.898 22.8						1000
	DBVBL2-13	DBVL2-13	.118 3.0								1000
	DBVB2-14	DBV2-14	.094 2.4	.551 14.0	.937 23.8						1000
	DBVBL2-14	DBVL2-14	.118 3.0								1000
	DBVBS2-18	DBVS2-18	.079 2.0	.709 18.0	1.094 27.8						1000
	DBVB2-18	DBV2-18	.087 2.2								1000
	DBVBL2-18	DBVL2-18	.110 2.8								1000
12-10 A.W.G. 4-6 mm ²	DBVB5-10	DBV5-10	.110 2.8	.394 10.0	.906 23.0	.512 13.0	.252 6.4	.142 3.6	.039	IZUMI MODEL 5 WITH DIE INDEX COLOR:YELLOW OR K.S. MODEL KST2000A HRI-126 WITH DIE INDEX COLOR:YELLOW	500
	DBVBS5-14	DBVS5-14	.157 4.0	.551 14.0	1.063 27.0						500
	DBVB5-14	DBV5-14	.177 4.5								500
	DBVBS5-18	DBVS5-18	.079	.709 18.0	1.220 31.0						500
	DBVB5-18	DBV5-18	.177 4.5								500

(I) (I) ALL LISTED

⊚: NOT UL AND C-UL LISTED