

產品說明 PRODUCT DESCRIPTION

- *類別: ■ ■ 歐規厚肉耐熱汽車花線
- *導體: 符合 ISO 6722 規範軟銅絞線 Stranded copper conductor
- *絕緣: PVC 材質, 符合 ISO 6722 及 ROHS 規範 PVC Insulation
- *耐溫: -40~125℃
- *多種顏色選擇 Any colors for customized



FLYW 歐規厚肉耐熱汽車花線，適用於汽車、機車及各式運送工具之歐規厚肉低壓絕緣花線，符合 ISO 6722 規範。

FLYW Temperature-resistant low tension wire with thick wall insulation, suitable for automobiles, motorcycles, and other motor vehicles. ISO 6722 compliant.

FLYW | ISO Thick Wall Heat-Resistant PVC Wire

公稱截面積 mm ²	導體結構 mm X no.	絞合外徑 Overall Diameter	絕緣厚度		完成外徑 最大	外被披覆 Material
			標準	最小		
0.50 mm ²	0.20 mm / 16	1.0 mm	0.6 mm	0.48 mm	2.3 mm	PVC
0.75 mm ²	0.20 mm / 24	1.2 mm	0.6 mm	0.48 mm	2.5 mm	PVC
1.0 mm ²	0.20 mm / 32	1.3 mm	0.6 mm	0.48 mm	2.7 mm	PVC
1.5 mm ²	0.25 mm / 30	1.6 mm	0.6 mm	0.48 mm	3.0 mm	PVC
2.0 mm ²	0.30 mm / 30	1.9 mm	0.6 mm	0.48 mm	3.3 mm	PVC
2.5 mm ²	0.25 mm / 50	2.1 mm	0.7 mm	0.56 mm	3.6 mm	PVC
3.0 mm ²	0.31 mm / 45	2.4 mm	0.7 mm	0.56 mm	4.1 mm	PVC
4.0 mm ²	0.30 mm / 56	2.6 mm	0.8 mm	0.64 mm	4.4 mm	PVC
6.0 mm ²	0.30 mm / 84	3.2 mm	0.8 mm	0.64 mm	5.0 mm	PVC
10 mm ²	0.40 mm / 80	4.1 mm	1.0 mm	0.80 mm	6.5 mm	PVC
16 mm ²	0.40 mm / 126	5.2 mm	1.0 mm	0.80 mm	8.3 mm	PVC
25 mm ²	0.40 mm / 196	6.5 mm	1.3 mm	1.04 mm	10.4 mm	PVC
35 mm ²	0.40 mm / 276	7.7 mm	1.3 mm	1.04 mm	11.6 mm	PVC
50 mm ²	0.40 mm / 396	9.2 mm	1.5 mm	1.20 mm	13.5 mm	PVC
70 mm ²	0.50 mm / 360	11.0 mm	1.5 mm	1.20 mm	15.5 mm	PVC